/our models

Our goal: your comfort
Our specialty: quality wall-mounted split a/c systems
Our strength: one of the quietest systems
Our identity: a dynamic Canadian based company

Outdoor Unit

9&12 000 BTU

15&18 000 BTU

24 000 BTU

SPECIFICATIONS

MODELS				9SRA-HE	12SRA-HE	15SRA-HE	18SRA-HE	24SRA-HE
Performance ratings								
Nominal capacity		BTU/h	Cooling	9 000	12 000	15 000	18 000	24 000
S.E.E.R		BTU/hW	Cooling	15	13.5	14	13	13
Refrigerant type				R-410A	R-410A	R-410A	R-410A	R-410A
Dehumidifying capacity		Pt./H		1.9	3.1	3.5	4.1	5.2
Airflow circulation (High)		CFM		382	441	559	647	765
Indoor sound rating (High-Medium-Low)		dB(A)		44-40-33	45-42-34	47-44-40	48-44-40	52-49-45
Outdoor sound rating		dB(A)		50	52	55	56	59
Temperature	Indoor air intake	°F (°C)	Maximum	95 (35)	95 (35)	95 (35)	95 (35)	95 (35)
			Minimum	64 (18)	64 (18)	64 (18)	64 (18)	64 (18)
	Outdoor air intake	°F (°C)	Maximum	109 (43)	109 (43)	109 (43)	109 (43)	109 (43)
			Minimum	32 (0)	32 (0)	32 (0)	32 (0)	32 (0)
Electrical data								
Voltage rating		V		115	115	115	208~230	208~230
Frequency / Phase		Hz / ø		60 / 1	60 / 1	60 / 1	60 / 1	60 / 1
Running amperes		A	Cooling	7.7	10.6	10.7	7.9	10.5
Minimum circuit ampacity		A		15	15	15	15	20
Maximum overcurrent protection (Time delay fuse or HACR type circuit breaker)		A		15	25	25	20	25
Refrigeration tubing								
Connection method				Flare	Flare	Flare	Flare	Flare
Refrigerant tube outer diameter		in.	Narrow	1/4	1/4	1/4	1/4	3/8
			Wide	1/2	1/2	1/2	5/8	5/8
Limit of tubing lenght		ft.		49	49	49	49	49
Limit of elevation difference between the two units		ft.		20	20	20	20	20
Dimensions & weight								
Indoor unit	Dimensions	in.	Width	31 1/2	31 1/2	38 3/4	38 3/4	42 1/2
			Height	10 7/8	10 7/8	12 5/8	12 5/8	13
			Depth	8 1/4	8 1/4	7 1/2	7 1/2	9 1/4
	Weight	lbs	Shipping	24	22	33	33	39
			Net	19	19	28	28	35
Outdoor unit	Dimensions	in.	Width	31 3/4	33 7/8	33 7/8	37 1/2	38 1/4
			Height	23 1/2	25 5/8	25 5/8	33 3/4	37 1/2
			Depth	11 1/4	12	12	13 3/4	14 1/2
	Weight	lbs	Shipping	92	101	101	138	149
			Net	88	94	94	119	141

*Note: Design and specifications are subject to change without notice for product improvement.

C US

BORA A/C
www.bora-air.com
450.437.2420 ext. 2
12775, rue Brault, Mirabel (Quebec) Canada J7J 0C4

authorized dealer

B00002-V00

An ecological comfort... BORA A/C

BORA WARRANTY part and labor 5 years

SEER 15

R-410A

wall-mounted split a/c systems

/ up to 15 SEER rating

BORA WARRANTY 5 years on parts, labour and compressor. Design and engineering by Bora a/c in Canada.

AIR QUALITY The Bora wall-mounted units have an absorbant carbon filter which allows a better air quality.

DIMENSIONS Our Bora high efficiency wall-mounted units, now has reduced dimensions that will integrate easier to all environments.

ENVIRONMENT (R-410A) We use in all our systems R-410A refrigerant, made to prevent further deterioation of the ozone layer which protects us from harmful UV sun rays.

ENERGICALLY EFFICIENT The Bora models with high efficiency will allow you to reduce considerately your energy consumption. You will obtain superior cooling capacity at a lower price.

/about

For the Bora wall-mounted **(up to) 15 SEER** units, we use the **REFRIGERANT R-410A**, which represents a susbstancial energy economy, compared to the 10 SEER model. They also maintain an ideal degree of comfort and are esthetically appealing. The Bora wall-mounted unit will intergrate easily to your environment because of its reduced dimensions.

FEATURES:

> 5 operating modes:
- cooling
- automatic
- fan
- dehumidifying
- sleep;

> 3 fan speeds plus automatic fan operation:
- low
- medium
- high
- automatic;

> Automatic restart function after power failure;

> 24-hour programming;

> Louvers with 5 positions and automatic swivel.

/remote control

FUNCTIONS:

: on / off button

MODE : 5 operating modes:
cooling | auto | fan | dehumidifying | sleep

: fan speed adjustment button

CLOCK : clock button

: timer setting buttons

HR / MIN : clock setting buttons

: sleep button

: airflow sweep button

°C / °F : °C / °F switch button

COOLER / WARMER : temperature adjustment buttons

/features

Built-in **low ambient** fan cycling control

Extremely silent high performance fan

Compressor with **R-410A** refrigerant

Anti-vibration rubber pads

Compressor sound **blanket**

DC motors with variable speeds

9, 12 & 15 000 BTU operating on **115V**

Greater airflow

A **look** that will integrate easily to your environment

Reduced dimensions