

Model	CS/CU-E9EKK	CS/CU-E12EKK	CS/CU-E18EKK	CS/CU-E21EKK
Cooling Capacity (Min ~ Max) (Btu/h)	4,100 ~ 10,200	4,100 ~ 13,100	4,400 ~ 19,700	4,400 ~ 23,400
SEER (Btu/hW)	17.0	17.0	16.5	16.5
Heating Capacity (Min ~ Max) (Btu/h)	4,100 ~ 16,500	4,100 ~ 21,000	4,400 ~ 26,200	4,400 ~ 28,200
HSPF (Btu/hW)	7.20	7.20	7.00	7.00
Voltage	208V - 230V	208V - 230V	208V - 230V	208V - 230V
Running Current	3.5 - 3.0A	5.3 - 4.6A	7.9 - 7.3A	10.7 - 9.7A
Power Input (Heating)	650W (1,000W)	1000W (1,450W)	1600W (1,850W)	2150W (2,150W)
Indoor Noise Level (Hi/Lo) (Heating)	40/28 (42/29) dB	43/31 (44/35) dB	45/39 (46/39) dB	46/39 (47/39) dB
Outdoor Noise Level (Hi) (Heating)	45 (46) dB	45 (47)dB	47 (47) dB	48 (49) dB
Moisture Removal (Pt/h)	1.9	2.7	3.8	5.5
Air Circulation (Indoor) (cfm) (Heating)	280 (310)	310 (340)	480 (560)	520 (580)
Height (Indoor Unit)	11 1/32 in	11 1/32 in	10 13/16 in	10 13/16 in
Width (Indoor Unit)	31 15/32 in	31 15/32 in	39 9/32 in	39 9/32 in
Depth (Indoor Unit)	7 7/32 in	7 7/32 in	9 1/16 in	9 1/16 in