



# R4A3

## EFFICIENT 13 SEER AIR CONDITIONER ENVIRONMENTALLY SOUND R-410A REFRIGERANT

### 1½ THRU 5 TONS SPLIT SYSTEM

### 208 / 230 Volt, 1-phase, 60 Hz

#### REFRIGERATION CIRCUIT

- Copeland Scroll™ compressors on all models
- Copper tube / aluminum fin coil

#### EASY TO INSTALL AND SERVICE

- Easy Access service valves on all models
- External high and low refrigerant service ports
- Only two screws to access control panel
- Factory charged with R-410A refrigerant

#### BUILT TO LAST

- Pre-painted cabinet finish over galvanized steel
- Coated inlet grille with 2" spacing standard, alternate models available with ¾" grille spacing for extra protection
- 5 year compressor limited warranty
- 5 year coil limited warranty
- 5 year parts limited warranty



Rated in accordance with ARI Standard 210. Certification applies only when used with proper components as listed with ARI.

Model Number	Size (tons)	Nominal BTU/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions heightxwidthxdepth (in)	Ship / Operating Weight (lbs)	Price
R4A318AKA	1½	18,000	11.7	20	24 <sup>13</sup> / <sub>16</sub> x 23 <sup>1</sup> / <sub>8</sub> x 23 <sup>1</sup> / <sub>8</sub>	120 / 104	
18GKA	same model with ¾" spacing inlet grille					124 / 108	
R4A324AKA	2	24,000	17.6	30	24 <sup>13</sup> / <sub>16</sub> x 23 <sup>1</sup> / <sub>8</sub> x 23 <sup>1</sup> / <sub>8</sub>	123 / 107	
24GKA	same model with ¾" spacing inlet grille					127 / 111	
R4A330AKA	2½	30,000	16.8	25	28 <sup>7</sup> / <sub>16</sub> x 23 <sup>1</sup> / <sub>8</sub> x 23 <sup>1</sup> / <sub>8</sub>	126 / 110	
30GKA	same model with ¾" spacing inlet grille					130 / 114	
R4A336AKA	3	36,000	17.6	30	35 <sup>3</sup> / <sub>16</sub> x 23 <sup>1</sup> / <sub>8</sub> x 23 <sup>1</sup> / <sub>8</sub>	139 / 122	
36GKA	same model with ¾" spacing inlet grille					144 / 127	
R4A342AKA	3½	42,000	23.5	40	31 <sup>19</sup> / <sub>16</sub> x 31 <sup>3</sup> / <sub>16</sub> x 31 <sup>3</sup> / <sub>16</sub>	187 / 164	
42GKA	same model with ¾" spacing inlet grille					195 / 172	
R4A348AKA	4	48,000	26.2	40	38 <sup>5</sup> / <sub>8</sub> x 31 <sup>3</sup> / <sub>16</sub> x 31 <sup>3</sup> / <sub>16</sub>	206 / 181	
48GKA	same model with ¾" spacing inlet grille					217 / 190	
R4A360AKA	5	60,000	34.4	50	28 <sup>7</sup> / <sub>16</sub> x 31 <sup>3</sup> / <sub>16</sub> x 31 <sup>3</sup> / <sub>16</sub>	216 / 190	
60GKA	same model with ¾" spacing inlet grille					224 / 198	